

1	2	3	4	5	6	7
USU34-1800EF	1	2	2	3	1	1
USU34-2100EF	1	2	2	4	1	1
USU34-2300EF	1	2	2	4	1	1
USU34-2540EF	1	2	2	4	1	1

Beyerle US L.L.C., ABP-Beyerle, it's subsidiaries and agents are not responsible or liable for damage or injury to any persons or property due to improper installation of it's products. All liabilities reside solely with the installer.



Beyerle US L.L.C. 1294 Logan Circle, Atlanta, GA 30318 Toll Free: Phone (877) 333-2620, Fax (877) 202-2563, www.beyerle-us.com, info@beyerle-us.com

qualified licensed contractor.

Be sure to tighten all screw connections one week after starting to use the sliding door fittings!

Never use scouring agents to clean the sliding door fittings; rather use commercially available stainlesssteel cleaners!

•	Screw on
9,	Screw on
Ô	Loosen / Tighten
¥ ∧	Install
90°	At right angle
622	Drill

Attention

Screw on

0

Dowels Adjust Set

Level

Measure Mark

 \bigcirc Visual inspection

Perpendicular

Special-K tool

2 people required

Measure 10 20

Clarify questions

See instructions

G Secure

Installation instructions for glass doors (5/16" - 1/2" thickness)



Complete-sets (standard model for 5/16" - 1/2" glass doors)

Set Unotec Home Art. No.	A inch	B inch	C Each	D inch	E max. inch	F inch	G inch	H max. inch (H = E - F + 1")
USU34-1800EF	70 7/8"	30 5/16"	3	29 1/2" - 35 7/16"	98 7/16"	1/4" - 3/8"	2 3/8"	99 1/8"
USU34-2100EF	82 11/16"	24 1/8"	4	35 13/16" - 39 3/8"	98 7/16"	1/4" - 3/8"	2 3/8"	99 1/8"
USU34-2300EF	90 9/16"	26 3/4"	4	39 3/4" - 44 1/16"	98 7/16"	1/4" - 3/8"	2 3/8"	99 1/8"
USU34-2540EF	100"	29 15/16"	4	44 1/2" - 49 3/16"	98 7/16"	1/4" - 3/8"	2 3/8"	99 1/8"

JSU34-USA

Right to make technical changes reserved - Dimensions in inches - Version 04.2008 © by ABP-Beyerle GmbH

Sliding door fittings **Unotec Home**

Beyerle US



Right to make technical changes reserved - Dimensions in inches - Version 04.2008 BeyerleUS © by ABP-Beyerle GmbH

Installation instructions Sliding door fittings **Unotec Home** for glass doors (5/16"-1/2" thickness)